


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



**SPECIFICATION:**

- Frequency Range: 10 to 1000 MHz
- Isolation: 19dB Typ.
- VSWR: 1.30:1 Max.
- Insertion Loss: 1.5dB Max.
- Amplitude Unbalance: ±0.4dB Max.
- Phase Unbalance: ±5° Max.
- Impedance: 50 Ohm
- Operating Temperature: -40°C to +85°C

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://WWW.MCLI.COM">http://WWW.MCLI.COM</a>	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: <b>2-WAY POWER DIVIDER</b>		
DRAWN: Paiboon Luekhamhan		PART NO. <b>PL2-5-S/BF</b>		
DATE: 05-20-2009	DATE: 05-20-2009	CAGE CODE: OD2L5	SIZE: A	REV: N/A
APPROVED: T. Nguyen		DO NOT SCALE THE DRAWING		DWG NO. <b>84487</b>
THIRD ANGLE PROJECTION 				